



Field Cultivator Inspection

Heavy Vehicle Inspection | <https://heavyvehicleinspection.com/>

| | | | | | |
|-----------|--|------|--|-----------|--|
| Inspector | | Date | | Signature | |
|-----------|--|------|--|-----------|--|

FIELD CULTIVATOR CHECK LIST

| Inspection Item | Note | Good | Repair | Replace | NA |
|--|------|------|--------|---------|----|
| Visually check all guards are secure and operate correctly (check latches / locks and interlocks if fitted) | | ■ | ■ | ■ | ■ |
| Visually check that the power take off and three point linkage guards including securing chains are to manufacturer's specification. | | ■ | ■ | ■ | ■ |
| Visually check that the rear guard is adjusted to the correct height for work to be undertaken. | | ■ | ■ | ■ | ■ |
| Ensure that no person or animal can be injured whilst the machine is operating. | | ■ | ■ | ■ | ■ |
| Verify the availability and condition of personal protective equipment. | | ■ | ■ | ■ | ■ |
| Visually check all guards are secure and operate correctly (check latches / locks and interlocks if fitted) | | ■ | ■ | ■ | ■ |
| Check the cultivator tines and spacing for damage or cracks | | ■ | ■ | ■ | ■ |
| Ensure that the cultivator shear bolts are in sound condition and replace if damaged. | | ■ | ■ | ■ | ■ |
| Check that the power take off guard, and clutch guard is free from any foreign material. | | ■ | ■ | ■ | ■ |
| Check the three point linkage, pinions, securing chains are in sound condition if damaged | | ■ | ■ | ■ | ■ |
| Lubricate lightly according to manufacturer's specification. | | ■ | ■ | ■ | ■ |
| Lubricate all points in accordance with the manufacturer's specification. | | ■ | ■ | ■ | ■ |
| Check the power take off guard if fitted is functioning and in good sound condition | | ■ | ■ | ■ | ■ |
| xfgvxf | | ■ | ■ | ■ | ■ |
| Check the availability of spare parts e.g. tines, spacers, chain drives if fitted, etc. | | ■ | ■ | ■ | ■ |